

**ELECTROPHORESIS MEMBER AND ELECTROPHORESIS DEVICE USING SAME**

Patent Number: JP11183437  
Publication date: 1999-07-09  
Inventor(s): INOUE SHINJI; NAKANISHI HIROAKI  
Applicant(s): SHIMADZU CORP  
Requested Patent: JP11183437  
Application Number: JP19970365831 19971222  
Priority Number(s):  
IPC Classification: G01N27/447  
EC Classification:  
Equivalents:

---

**Abstract**

---

**PROBLEM TO BE SOLVED:** To enable the highly accurate measurement of a trace sample in a capillary part.

**SOLUTION:** Potential differences are provided for both ends of a channel groove 53 for separation filled with a liquid for electrophoresis to cause a sample to migrate. An insulating film/semiconductor interface formed of a silicon nitriding film 29 and a silicon substrate 21b formed so as to cover the channel groove 53 for analysis is irradiated with light modulated into a predetermined frequency from the side of the silicon substrate 21b by a laser light source 47 and is, for example, impressed with a bias voltage V of 1 V by a voltage impressing power source 51, and a generated optical a.c. current I is measured by an optical a.c. current measuring device 49. As a result, it is possible to detect changes in the pH values of a capillary part irradiated with laser light as changes in the optical a.c. current I, and it is possible to detect even a trace sample without impairing detection sensitivity.

---

Data supplied from the esp@cenet database - I2